Classic GI36 & GI30

Medium & Small Wood Insert



GI36 with black door,regular faceplace.

Your open masonry fireplace can allow as much as 90% of your Fire's heat to escape out the chimney. By adding a Regency Classic Fireplace insert, you will keep the heat in your home. Regency inserts are ready to install and fit easily into your existing fireplace. Increase The value of your home and decrease your monthly heating bill.

總代理: 台灣虹麗企業有限公司 服務電話: (04)7721501. 0935-396358

展示中心: 台中市西屯區大墩20街116號3F-2(歡迎預約參觀)

www.beaubow168.com





GI30 with black door, regular faceplace.

Standard Features

- ◆ EPA Certified
- ◆ Single rod draft control
- ◆ Airwash system
- ◆ Brick-lined firebox

Optional Features

- ◆ Cast iron door in gold,black**.
- Regular or oversize faceplate
- 2-speed blower.
- Screen door.
- Bottom 1 piece faceplate

Specifications

-1		
	GI36	GI30
Maximum BTU*	80000	50000
Typical Sq.Ft.Heated	1000-2200	600-1600
Optimum Efficiency	72%	72%
Maximum Log Size	22	16
Burm Time (Typical)*	8	8
Emissions (grams/hr)	3.0	3.0
Flue Size	6"	6"

^{*}Length of burm time and BTU range depend on type of wood, moisture content, climate conditions and installation.